

# SOLAMENT REFLECT i

ACRYLIC PAINT INTERIOR

## TECHNICAL DATA SHEET

As of: 2 May 2024  
Page 1/3



**aerodurit** **SPECIALISED**

# SOLAMENT REFLECT i

Advantages	
Heat reflection effect through thermal pigmentation	✓
Thermo-insulating, -regulating	✓
Breathable	✓
Very supple, good coating properties	✓
Washable and light-resistant	✓
Water-repellent	✓
Special Applications	
Interior	✓



# SOLAMENT REFLECT <sup>i</sup>

## ACRYLIC PAINT INTERIOR

# TECHNICAL DATA SHEET

As of: 2 May 2024  
Page 2/3

aerodurit<sup>®</sup> SOLAMENT REFLECT <sup>i</sup> is a water-based, permeable, fibre-reinforced interior paint based on plasticizer-free acrylic dispersions. Contains thermo-insulating and thermo-regulating pigments.

### PROPERTIES

Breathable, excellent moisture- and climate-regulating properties, strong heat reflection effect, improves thermal insulation and retention values, water-repellent, dirt-dissolving (photocatalysis), environmentally friendly, washable, acid- and light-resistant, very supple with good coating properties and easy to apply.

### APPLICATION

aerodurit<sup>®</sup> SOLAMENT REFLECT <sup>i</sup> Acrylic Paint is designed for use as a heavy duty preventive measure for adverse room climate (rooms with high humidity such as utility rooms, kitchens, bathrooms). Its temperature-regulating properties ensure almost even heat distribution on the wall surfaces, actively reducing the formation of condensation and mould in cooler corners. For mineral substrates such as plaster, concrete, wood and sound old coatings as well as substrates suitable for emulsion paints (plasterboard, Fermacell etc.). The guidelines of VOB, part C / DIN 18363, paragraph 3 and the respective BFS leaflets must be observed.

### TECHNICAL DATA

Water absorption w <sub>24</sub> (kg/m <sup>2</sup> 24 h)	0.10
Water vapour permeability sd (m)	ca. 0.015 kg/m <sup>2</sup> 24 h
Water vapour diffusion equivalents air layer thickness	ca. 1.1 m
Application temperature (ambient air, object and material)	+ 5 °C to + 30 °C
VOC threshold value	Cat. A/cWb = 40 g/l (2010)
VOC maximum content	1 g/l
Grain grade in compliance with DIN EN ISO 2431	Fine
Wet abrasion class in compliance with DIN EN 13300	Class 2
Coating ability	Class 2
Gloss in compliance with DIN EN ISO 2813	Matt
Fire resistance	A1 / non-combustible

### SUPPLY FORM

Trading Unit	Delivery Unit
5 l bucket	60 pcs./Euro pallet
15 l bucket	24 pcs./Euro pallet

### PRODUCT YIELD

Undiluted per application from 150 ml/m<sup>2</sup>, per litre ca. 6–7 m<sup>2</sup> (depending on substrate structure and absorbency). The actual consumption can be determined by means of a test coat.



### PREPARATION AND MIXING

aerodurit<sup>®</sup> SOLAMENT REFLECT <sup>i</sup> Acrylic Paint can be applied directly after **thorough stirring**. If necessary, stir repeatedly during application. For use as a primer, can be diluted up to 5% with fresh water (for absorbent substrates – see Surface Pretreatment).



### COLOURING

White. Tint only with suitable tinting concentrates. Numerous factory-made colour tints derived from the NCS colour system are available.



### NOTES AND PRECAUTIONS

Carefully cover the area around the surface to be coated. Wear gloves and safety goggles (not glasses). Avoid skin and eye contact. Remove splashes immediately with plenty of water. Clean tools thoroughly with water immediately after use. Do not use in direct sunlight, rain, strong wind, when there is a risk of frost or a relative humidity above 80%. Always use paint from the same batch to achieve a uniform appearance. Do not mix with other colours.

# SOLAMENT REFLECT

## ACRYLIC PAINT INTERIOR

aerodurit<sup>®</sup> Putz- & Betontechnologie GmbH  
Albert-Reis-Str. 7 · D-88356 Ostrach  
Tel.: +49 (0) 75 85 92 44 990  
Fax: +49 (0) 75 85 92 44 999  
E-Mail: [tm@aerodurit.com](mailto:tm@aerodurit.com)  
[www.aerodurit.com](http://www.aerodurit.com)

## TECHNICAL DATA SHEET

As of: 2 May 2024  
Page 3/3



### SURFACE PRETREATMENT

Newly plastered surfaces must be completely cured, respectively carbonated (e.g. lime plasters, see technical data sheet manufacturer). Cracks in the substrate must be professionally repaired beforehand. All substrates must be clean, dry, stable, free of dust, blooming and separating agents. Always remove dirt, film-forming release agents such as mould wax/oils or sintered layers. Substrates that cannot be consolidated or provide insufficient adhesion must be completely removed. Chalking, crumbly and absorbent substrates have to be stabilised by suitable measures (use aerodurit<sup>®</sup> FIXATIVE F-1 special fixing agent, not deeppenetrating primer). If in doubt, apply a trial coat



### PROCESSING

Ensure uniformity in the application and distribution of the material in order to achieve the layer thickness to ensure the functionality. Apply the paint with roller, brush or spray gun. For airless spraying, if possible, attach a filter in front of the intake manifold. Two coats are necessary. Dust-dry and re-paintable after ca. 2 hours (at +20 °C and 65 % relative humidity).

Ensure adequate ventilation.

### STORAGE

Store weatherproof and frost-free on wooden pallets in a cool, dry room. Reseal opened packaging immediately. Closed packaging has a shelf life of 8 months from the production date under proper storage conditions. Keep out of the reach of children.

### DISPOSAL

Allow paint residues that are no longer required to dry completely and dispose of them like household waste or hand them over for disposal. Hand over liquid material for disposal. Waste code no.: 08 01 12. Local regulations are to be observed and complied with.

For further details please refer to the safety data sheet.

The specifications contained in this technical data sheet are based on years of proven experience by the company aerodurit<sup>®</sup>. A liability for the general validity of the individual data and recommendations, must, however be ruled out due to the varying processing conditions, as the application and processing methods are beyond our control.

The general rules of construction engineering must be adhered to. The data of internal or third-party monitoring may vary on the construction site due to processing methods, intensity of the mixing, technical specifications of the machines, adhesion of the substrate, application thickness, environmental influences, and the age of the material (refer to »Forschungsgemeinschaft Kalk und Mörtel e.V.« (research community lime and mortar), Report on norms, practical experience and theory, »26th Aachener Baustofftag«).

Previous data sheets become void through the publication of this data sheet. Stay up-to-date! Refer to [www.aerodurit.com](http://www.aerodurit.com) for the most current version of our data sheets.